

Filter Elements

Disposable Grades & Dimensions

All disposable filter elements have a part number arranged in three sections, for example 25.64.7K

The first part refers to the inside diameter of the element in millimetres, the second figure refers to the overall length in millimetres and the third part is the designation for the grade and binder.

Standard Sizes

Filter Elements are available in a wide range of standard diameters and lengths. These are based on traditional industry standard sizes and allow the elements to be installed in other proprietary equipment.

12.32.□ 12.57.□ 25.64.□ 25.127.□ 25.178.□ 38.58.□ 38.152.□ 45.127.□ 51.230.□ 51.89.□ 51.476.□ 63.762.□

Replace the □ in the part numbers shown with the grade selected from the tables below. More information about the binder types can be found on page CF/2.0a/021.

Efficiency

Each filter element type is available in a selection of grades covering a efficiency range from coarse bulk contamination removal and the essentially complete removal of submicron particles.

The standard grades are shown in the tables below.

Particulate Applications - Gas								
% Removal of 0.1 micron particles								
Binder		Max. Temp.	+99.99998%	+99.9999%	+99.99%	+99.5%	+95%	+75%
E	Epoxy Ester	300°F	3E	4E	5E	6E	7E	8E
K	PVDF Fluorocarbon	300°F	3K	4K	5K	6K	7K	8K
S	Silica Inorganic	930°F	3S	4S	5S	6S	7S	8S
L	Silicone	390°F		4L		6L		

Coalescing Applications - Gas						
% Removal of 0.1 micron particles & aerosols						
Binder		Max. Temp.	+99.99%	+99.5%	+95%	+75%
CE	Epoxy Ester	300°F	5CE	6CE	7CE	8CE
CK	PVDF Fluorocarbon	300°F	5CK	6CK	7CK	8CK
CR	PVDF Fluorocarbon	300°F	5CR	6CR	7CR	8CR
CS	Silica Inorganic	930°F	5CS	6CS	7CS	8CS
W	Silicone	390°F	5W	6W	7W	8W

Particulate Applications - Liquid								
+98% Removal of particles at stated size								
Binder		Max. Temp.	0.3 µm	1 µm	2 µm	8 µm	25 µm	75 µm
E	Epoxy Ester	300°F	3E	4E	5E	6E	7E	8E
K	PVDF Fluorocarbon	300°F	3K	4K	5K	6K	7K	8K
S	Silica Inorganic	930°F	3S	4S	5S	6S	7S	8S

Special Sizes

Special size filter elements can also be manufactured in a wide range of different diameters and lengths.

Inside Diameters - 0.28" to 5.90"

Lengths - 0.35" to 39.35"

Please enquire with any specific requirements.